

CERTIFICATE

No. U6 001498 0104 Rev. 00

Holder of Certificate: **Jiangsu Kegou Power Electronics Co., Ltd.**
No.16, Zhixi Road
Industrial Concentration District
Zhixi Town, Jintan District
213251 Changzhou City, Jiangsu Province
PEOPLE'S REPUBLIC OF CHINA

Certification Mark:



Product: **Electronic controlgear for LED modules
(LED dimmable driver)**

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. It is not permitted to alter the certification mark in any way. In addition, the certificate holder must not transfer the certificate to third parties. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 64142210339201

Date, 2021-09-02



(Richard Xu)

CERTIFICATE

No. U6 001498 0104 Rev. 00

Model(s): KDMH014S0350DR43, CC14W200-350CG DALI,
KDMH020S0500DR43, CC20W350-500CG DALI,
KDMH032S0800DR43, CC32W500-800CG DALI,
KDMH040S1000DR43, CC40W850-1000CG DALI,
KDMH048S1200DR44, CC48W1050-1200CG DALI

Brand Name: KeGuPower, KGP



Parameters: Rated Input Voltage: 220-240 VAC
Rated Frequency: 50/60Hz
Rated output: See model list in page 3
Protection against Electric Shock: Class II; SELV (for
independent type with
terminal cover)
SELV (for built-in type
without terminal cover)
Degree of Protection: IP20 (for independent type with
terminal cover)
Method of Installation: Independent (with terminal cover)
Built-in (without terminal cover)
Type of Output: Constant current type
ta; tc: See model list in page 3

Tested according to: EN 61347-1:2015/A1:2021
EN 61347-2-13:2014/A1:2017
EN 62384:2006/A1:2009

Production Facility(ies): 001498, 076089

CERTIFICATE

No. U6 001498 0104 Rev. 00

Model list

Model I (KEGU)	Model II (KGP)	Max. Output current (mA)	Output voltage (Vdc)	Max. Output power (W)	ta; tc (°C)
KDMH014S0350DR43	CC14W200-350CG DALI	200	28-40; No load: 55	8	-20~50; 75
		250		10	
		300		12	
		350		14	
KDMH020S0500DR43	CC20W350-500CG DALI	350	28-40; No load: 55	14	-20~50; 75
		400		16	
		450		18	
		500		20	
KDMH032S0800DR43	CC32W500-800CG DALI	500	28-40; No load: 55	20	-20~50; 85
		600		24	
		700		28	
		800		32	
KDMH040S1000DR43	CC40W850-1000CG DALI	850	28-40; No load: 55	34	-20~50; 85
		900		36	
		950		38	
		1000		40	
KDMH048S1200DR44	CC48W1050-1200CG DALI	1050	28-40; No load: 55	42	-20~50; 85
		1100		44	
		1150		46	
		1200		48	